

# DATA SHEET

## 3120PPS-B 20 Gauge Polypro Tip



### Product Description

High quality moulded dispense tips in 20 gauge. Burr free polypropylene 0.5" long shaft. Double helix locking pink polypropylene hub. Inner diameter of 0.019" (0.48). Silicone free and industrial grade safe to 100 psi. Shaft will not scratch or damage sensitive surfaces.

### Typical Applications

Use these flexible tips for dots and beads of most liquids, adhesives, gels solvents, inks, primers and activators. Can be used with syringe barrels and dispensing valves.



Most ADL components are available to order from stock. Products are of the highest quality and compatible with most dispensing systems and valves. We also stock a range of high quality industrial grade Cyanoacrylate adhesives in 20g, 50g and 500g HDPE bottles. Please contact us if you require product samples or a quotation.

### Part Numbers

Part 3120PPS-B	20G 0.5" Pink x 50
Part 3120PP-B	20G 1.5" Pink x 50

### Technical Information

Part 3120PP-B	20G Pink 0.5" Tip
Max Fluid Pressure	Up to 100 psi
Construction	Polypro, polypro hub
Length	0.5"
ID	0.019" (0.48mm)
OD	0.034" (0.86mm)
Connection	Luer lock Double Helix

### Packaging

Tips are supplied in packs of 50 or bulk packs of 1000.

### Pricing and Lead Times

Our tips are competitively priced whether in a single box of 50 or in bulk packs of 1000. We hold extensive stocks and can ship for next day deliveries.

### Options

For machine dispensing, we recommend using these tips with our TS250 pneumatic dispensing systems.

### Health & Safety in Use

Tips are safe to 100 psi and silicone free, reducing risk of operator contact with the materials being dispensed and contamination of adhesives placed inside.

### Benefits

- Safe to 100 psi
- Compatible with most liquids
- Silicone free plastics
- UV filter plastic hub and shaft
- Polypro suitable for solvents & CAS
- Double helix locking shaft
- Shafts can be cut down to length
- Ends will not damage surfaces
- Available from stock

The data, information and values contained in this Technical Data Sheet have been obtained by specific tests conducted in a controlled environment, and should be used for guidance purposes only. Although we believe them to be reliable and accurate, users should always conduct their own tests in their specific working conditions to ensure that the product is suitable and effective for use. It is the user's sole responsibility to determine the suitability of the product for the application. Adhesive Dispensing Ltd cannot be held responsible for the results of procedures undertaken elsewhere, nor for the safeguarding of personnel or property, all of which is the duty of the user. Suitability of products or methods is discretionary. Therefore, warranties or implied usage obligations should not be attributed to, and are not the responsibility of, Adhesive Dispensing Ltd. Adhesive Dispensing Ltd are not liable for any financial loss or other damages incurred by the user as a result of the use of this product. Product dimensions and design are approximate and could be subject to change, without notice.